

INSTALLATION INSTRUCTIONS
KAWASAKI MULE FXT
2013-2016

TOOLS REQUIRED

DRILL DRIVER	13/32 DRILL BIT
2 CLAMPS	RATCHET
1/2 WRENCH	1/2 SOCKET

INSTALLATION OF BUMPER

1] INSTALL BUMPER UNDERNEATH BED RAILS. USING THE FRONT TABS OF BUMPER TO ALIGN WITH HOLE ON BACK OF BED (FOR PROPER ALIMENT) INSERT SUPPLIED 5/16 X 1 AND HARDWARE BOLT INTO HOLES; CLAMP BUMPER ON RAILS.

2] LIFT BED TO ASSURE PROPER CLEARANCE BETWEEN TIRES AND BUMPER. CLOSE BED TO LOCKING POSITION AND ADJUST ACCORDINGLY.

3] OPEN THE TAILGATE TO ASSURE PROPER CLEARANCE. ADJUST IF NECESSARY.

4] CENTER PUNCH ALL FOUR HOLES IN CENTER OF RAILS.

5] REMOVE BUMPER; DRILL ALL HOLES.

6] INSTALL BUMPER WITH PROVIDED 5/16 X 3 THROUGH THE HOLES DRILLED AND 5/16 X 1 BOLTS IN BACK OF BED RAIL WITH HARDWARE. ALIGN AND TIGHTEN.

INSTALLATION INSTRUCTIONS

KAWASAKI MULE FXT

2013-2016

8] IF INSTALLING TOUGH COUNTRY FLUSH MOUNTS INSTALL LIGHTS WITH SUPPLIED BOLTS. INSTALL SWITCH AND RUN WIRING TO LIGHTS AND BATTERY.